

# Canon i-Sensys MF9280Cdn Recommended Small Office MFD

Professional, convenient  
All-In-One colour solution  
for small workgroups

**i-SENSYS**  
MF9280Cdn

you can



Enhance your communications with high quality colour output and boost productivity with powerful SEND functionality. This compact and robust colour All-In-One is ideal for busy small workgroups.

**21 PPM COLOUR  
PRINTING AND  
COPYING**

**EASY OPERATION  
WITH INTUITIVE  
USER INTERFACE**

**ENERGY EFFICIENT**

**POWERFUL SEND  
FUNCTION MAKES  
SHARING DOCU-  
MENTS EASY**

**FULL INPUT AND  
OUTPUT DUPLEX  
CAPABILITIES**

**SEAMLESS  
INTEGRATION  
INTO MANAGED IT  
ENVIRONMENTS**

**LDAP SUPPORT**

**MEMORY MEDIA  
SLOT**

## Key features

- Colour laser All-In-One
- 21 ppm colour printing and copying
- High quality professional colour output
- Quick First-Print & energy efficient
- Network ready, PCL 5c/6 and PostScript Level 3 support
- Scan to email, network folder & USB memory key
- 3.5 inch (8.8cm) colour TFT display with Easy-Scroll Wheel
- Double-sided print/copy/scan/fax
- 50-sheet Duplex ADF
- 850 maximum paper capacity
- Energy efficient

## What's in the Box

Main unit, Cartridge 711 C/M/Y/K, Power cord, USB cable, Starter guide manual on CD, User software CD, Warranty card

## Dimensions (WxDxH)

546 mm x 527 mm x 632 mm

## Supported OS

**Windows** 7 / Server 2008 R2/ Server 2008/ Server 2003/ XP/ Vista/ 2000

**Mac OS X** version 10.4.9-10.6.X  
(Web distribution only)

**Linux** (Web distribution only)



PRINT



COPY



FAX



SCAN

**Canon**

# i-SENSYS MF9280Cdn

## Specifications



- 1 Flatbed & DADF
- 2 Intuitive user interface
- 3 Standard 250 sheet cassette
- 4 Cartridge 711:  
4 cartridges available:  
Black, Cyan, Magenta and Yellow

<b>MF9280Cdn</b>	
Machine type	Colour Laser All-In-One
Available functions	Print, Copy, Scan and Fax
<b>PRINTER</b>	
Print speed	Up to 21 ppm colour and mono (A4)
Printing method	Colour laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	600 x 600 dpi
Double sided printing	Automatic
Printer languages	UFRII-LT, PCL5c, PCL6, PostScript Level-3
Fonts	93 scalable, 10 bitmap (PCL)
Print margins	5 mm-top, bottom, left and right
Toner saver mode	Yes
Printing from memory media	Supported memory media USB memory key, CompactFlash®, Microdrive, Memory Stick®, Memory Stick Pro™, SD Memory Card®, and SDHC Memory Card, Memory Stick Duo™ <sup>1</sup> , Memory Stick PRO Duo™ <sup>1</sup> , Memory Stick Micro™ <sup>1</sup> , miniSD Card™ <sup>1</sup> , microSD Card™ <sup>1</sup>
Supported file systems:	FAT 16 and FAT 32
<b>COPIER</b>	
Copy speed	Up to 21 cpm colour and mono (A4)
First Copy Output Time (FCOT)	Approx. 12.5 seconds or less
Copy resolution	Up to 600 x 600 dpi
Copy modes	Text/Photo/Map (Default), Printed Image, Photo, Text
Double sided copying	2-sided to 2-sided (Automatic)
Multiple copy	Up to 99 copies
Reduction / Enlargement	50-200% in 1% increments
Toner saver mode	Yes
Other features	Frame Erase, Collate, 2 on 1, 4 on 1
<b>SEND Functions</b>	
Scan to file server	FTP, SMB
Scan to E-mail and i-Fax	SMTP, POP3, i-Fax (Simple mode)
Scan to USB memory key	Yes
File formats	TIFF, JPEG, PDF, PDF (Compact)
<b>SCANNER</b>	
Type	Colour
Scan resolution	Optical: Up to 600 x 600 dpi
Colour scanning depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN <sup>2</sup> , WIA <sup>2</sup>
Max. scan width	216 mm
<b>FAX</b>	
Modem speed	Super G3 33.6kbps (Up to 3 seconds/page <sup>3</sup> )
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual RX
Fax resolution	200 x 100 dpi: 8 pels/mm x 3.85 lines/mm 200 x 200 dpi: 8 pels/mm x 7.7 lines/mm 200 x 400 dpi: 8 pels/mm x 15.4 lines/mm 400 x 400 dpi: 16 pels/mm x 15.4 lines/mm
FAX memory	Up to 1,000 pages <sup>3</sup>
Speed dials	Max. 200 dials
Group dials/destinations	Max. 299 dials / Max. 299 destinations
Sequential broadcast	Max. 332 locations
Memory backup	1 hour
Double sided faxing	Yes (Transmit and Receive)
Other features	Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only)
<b>MEDIA HANDLING</b>	
Scanner type	Flatbed and Duplex Automatic Document Feeder (DADF)
Paper input (Standard)	250-sheet cassette 100-sheet multi-purpose tray 50-sheet DADF
Paper input (Option)	500-sheet cassette
Paper output	250-sheet
Media types	Plain paper, Recycled paper, Heavy paper, Transparency, Label, Envelope
Media sizes	Cassette and optional pedestal: A4, A5, B5, Legal, Letter, Executive Multi-purpose tray: A4, A5, B5, Legal, Letter, Executive, Statement, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5) Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm DADF: One-sided scanning: A4, A5, B5, Legal, Letter, Custom sizes (W x L): Max 215.9 mm x 355.6 mm Min. 128 mm x 139.7 mm Two-sided scanning: A4, Legal, Letter
Media weights	Cassette and optional pedestal: 60 to 120 g/m <sup>2</sup> Multi-purpose tray: 60 to 176 g/m <sup>2</sup> DADF: One-sided scanning: 50 to 105 g/m <sup>2</sup> Two-sided scanning: 64 to 105 g/m <sup>2</sup>

<b>INTERFACE &amp; SOFTWARE</b>	
Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, 2 x USB memory slot, Memory media slot
Operating System compatibility	Windows 7 /Server 2008 R2/ Server 2008/ Server 2003/ XP/ Vista/ 2000 Mac OS X version 10.4.9-10.6.x <sup>4,6</sup> Linux <sup>5,6</sup>
Software and printer management	NetSpot Device Installer, Canon Font Manager, Remote User Interface (RUI), Department ID Management
<b>GENERAL FEATURES</b>	
Duty cycle	Max. 65,000 pages per month
Warm-up Time	Approx. 60 seconds from power on
Memory	768 MB (shared)
Control panel	3.5 inch (8.8cm) colour TFT display with Easy Scroll-Wheel
Dimensions with trays (W x D x H)	546 mm x 527 mm x 632 mm
Installation space (W x D x H)	546 mm x 1140 mm x 792 mm 546 mm x 1140 mm x 1095 mm (with optional Cassette Feeding Unit-AC1 attached)
Weight	Approx 43.3 kg
Operating environment	Temperature: 10 to 32°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V (±10%) 50/60Hz (±2Hz)
Power Source	Maximum: Approx. 1210 W
Power Consumption	Active: Approx. 470 W Standby: Approx. 35 W Sleep mode: Approx. 1.2 W <sup>7</sup> Typical Electricity Consumption (TEC): 2.3 kWh/week Sound Pressure <sup>8</sup> : Active: 66 dB(A) or less Standby: 43 dB(A) or less
Noise Levels	
<b>CONSUMABLES</b>	
Cartridges	Cartridge 711 Black (6,000 pages <sup>9</sup> ) Cartridge 711 Cyan (6,000 pages <sup>9</sup> ) Cartridge 711 Magenta (6,000 pages <sup>9</sup> ) Cartridge 711 Yellow (6,000 pages <sup>9</sup> )
<b>ACCESSORIES/ OPTIONS</b>	
Items	CST.FEEDING UNIT-AC1 (500 sheet cassette) HANDSET-J1 (Telephone handset)

All specifications subject to change without notice

- [1] Using recommended adapter – not supplied
- [2] Scan to computer via USB connection is not supported
- [3] Based on ITU-T Standard Chart No. 1
- [4] Mac OS X support printing and PC faxing only
- [5] Linux supports printing only
- [6] Web distribution only
- [7] Lowest possible power consumption in sleep mode. If the device is connected to a network with other computers that are switched ON, the power consumption will be approximately 17 W
- [8] Declared noise emission in accordance with ISO 9296
- [9] Based on 5% coverage



Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com

English Edition  
© Canon Europa N.V., 2010