



Toshiba 520 600 720 850 Copier Specifications  
 Photocopier Datasheet - Printer Specs and Details

**e-STUDIO520**  
**e-STUDIO600**  
**e-STUDIO720**  
**e-STUDIO850**

# Document Manager

- High Volume e-BRIDGE system with up to 52/60/72/85 pages per minute output.
- Combining reliable performance, perfect reproduction quality, versatile paper handling and cost effectiveness
- High-End finishing with booklet finisher, hole punch and post inserter for preprinted sheets
- Multifunctional Toshiba e-BRIDGE controller for easy to use and intelligent communication in print, copy, scan, fax and email
- Highly secure data handling with private print, user authentication and optional scrambler board and harddisk overwrite kit





**e-STUDIO520** **e-STUDIO720**  
**e-STUDIO600** **e-STUDIO850**



<b>General</b>	Type Speed (both copy & print) Warm-up Time Paper Size  Standard Paper Capacity  Standard ADU Standard RADF Paper Weight  Memory size  Access Codes One touch Templates (Copy, Scan, Fax, e-File)  Dimensions (WxDxH) Weight	Console 52 / 60 / 72 / 85ppm Approx. 130 seconds A3-A5R (Feeder, Drawer & Bypass) A4 (Large Capacity Feeder) 2 x 500 sheets (Drawer), 2,500 sheets A4 (Large Capacity Feeder), 100 sheets (Bypass) (Automatic Duplexing Unit) (Reversing Automatic Document Feeder) 64-209gsm (paper supply & ADU) 50-127gsm (RADF) Main Memory 256MB + Page Memory 64MB = 320MB (shared), Hard Drive: 40GB+ (shared) Up to 1,000 Department / 10,000 User Codes 1 Public and up to 200 Private groups with each up to 60 individual buttons to customize the User Interface (including Dual-Function) 698mm x 789mm x 1,213mm Approx. 204kg
<b>Print*</b>	Page Description Languages Network Server OS  Interface  Resolution Additional Features	PCL6® compatible, PostScript® 3™ compatible Windows® Server2003 (32 bit), 2000, NT4.0, NetWare®, Citrix® MetaFrame XP™ 10BaseT/100BaseTX, Full-speed USB, Optional IEEE802.11b/802.11g(WiFi), Parallel (IEEE 1284), Bluetooth (HCRP) 2,400dpi x 600dpi (with smoothing) Proof Print, Private Print, Mixed-size Printing, Tab Print/Insertion, Magazine Sort, ...
<b>Copy</b>	First Copy Out Time  Resolution  Original Scan Speed Gradation Zoom  Copy mode Multiple Copying Additional Features	Less than 4 seconds (e-STUDIO520/600/720) Less than 3.5 seconds (e-STUDIO850) Scanning: 600dpi x 600dpi Printing: 2,400dpi x 600dpi (with smoothing) 71spm (A4) 256 Step Grayscale 25%-400% (Platen) 25-200% (RADF) in 1% increments, various pre-set ratios Text, Text/Photo (Default), Photo, Custom mode 1-9,999 Trimming/Masking, Mixed-size Copying, Copy to Box (e-Filing), Cover Sheet, Sheet Insertion, Magazine Sort, n-in-1, Annotation (Date/Time), Job Reservation (10 jobs), Job Build
<b>Scan*</b>	Resolution Original Scan Speed Scan mode File Format Scan functions	600, 400, 300, 200, 150dpi 83spm (A4, 300dpi), 71spm (A4, 600dpi) Text, Text/Photo, Photo Grey Scale (150-400dpi) TIFF (Single/Multi), PDF, JPEG 2-sided Scan, Image Rotation, Mixed Size Paper scanning, Scan to Email, Scan to file (SMB, FTP), Scan to Box (e-Filing)
<b>Fax*</b>	Communication mode Modem Speed Transmission Speed Compression Method Usable Circuits Additional Features Internet-Fax Network Fax	Super G3, G3 Max. 33.6 Kbps Approx. 3 seconds per page JBIG, MMR, MR, MH PSTN Group Dialing, Received Fax to Box (e-Filing), ... I-Fax is standard - Support T.37 (Simple Mode) Standard: Internet-Fax, Option: Super G3, G3, Driver for Windows® 98/Me/2000/XP/NT4.0
<b>e-Filing</b>	Functionality  Input Methods Box N/W access  Capacity	Storage documents in the system for Print On Demand, Retrieval, Editing over Web Tool Copy to, Scan to*, Print to*, Fax to*, I-Fax to* TWAIN Driver, File Downloader, e-Filing (web interface) 5GB, 1 public and 200 private boxes, 100 Folder per box, 400 documents per Box/Folder, 1,000 pages per document

\*optional

**OPTIONS**

- PRINTER KIT GM-1050**
- PRINTER/SCANNER KIT GM-2040**
- SCANNER KIT GM-4010**
- FAX BOARD GD-1170 \***
- WIRELESS LAN MODULE GN-1040**
- BLUETOOTH MODULE GN-2010**
- ANTENNA FOR WIRELESS LAN & BLUETOOTH GN3010**
- DATA OVERWRITE KIT GP-1060**
- PARALLEL INTERFACE KIT GF-1140\***
- SCRAMBLER BOARD GP-1040\***  
Additional Hard-Disk encryption
- PCI SLOT GO-1050**  
Prerequisite for installation of max two out of following three options: Scrambler Board, Parallel Interface Kit, Fax Board
- LARGE CAPACITY FEEDER MP-4004A**  
4,000 sheet A4 64-209gsm
- FINISHER MJ-1027**  
Up to 4,000 sheets in 2 trays  
50 sheets multi-position staple
- FINISHER MJ-1028**  
Same functionality as MJ-1027, plus saddle stitch for up to 15 sheet in A3/A4R
- FINISHER MJ-1029**  
100 sheet multiposition staple, plus saddle stitch for up to 15 sheet in A3/A4R
- HOLE PUNCH UNIT MJ-6003 (E/F)**  
Option for MJ-1027/MJ1028 Finisher
- INSERTER UNIT MJ-7001**  
Option for MJ-1027/MJ1028 Finisher  
Up to 100 sheets (60-256gsm)

\*PCI Slot GO-1050 is mandatory

TOSHIBA TEC UK  
 IMAGING SYSTEMS LTD  
 ABBEY CLOISTERS, ABBEY GREEN,  
 CHERTSEY, SURREY, KT16 8RB.  
 TEL 01932 580100 FAX 01932 580101  
 WWW.TOSHIBA.CO.UK/IMAGING

Technical data is subject to change without prior notice. Signed expressions are registered trademarks of their manufacturers. All rights reserved. Copyright © 2005 TOSHIBA TEC. EN1B5